

### APPLICATIONS:

Long Span shelving ideal for bulky / heavy loads:

- Industrial
- Auto Parts storage
- Banker Boxes
- Two-Tier Mezzanine

### APPEARANCE:

- Clean looking with common square front post
- Standard Colour: Grey with Particle&MDF board, plywood or steel shelving
- No bracing allows full accessibility from all sides
- Variety of accessories

### ACCESSORIES:

- Foot plates, post caps and top / bottom safety clips, provided on each section if required

### PRODUCT SPECIFICATIONS:

#### Components:

---

1. Upright 1" x 1½" tubular posts manufactured from 12 gauge cold rolled steel with slots on 2" centres and a half slot at the top of the post for a flush mounted top shelf. Posts shall be usable as common posts.
2. 'Z' shaped frame connectors: 14 gauge cold rolled steel with two (2) hooks and locking tab.
3. Front and back beams: cold rolled steel 1" high semi-v shaped with one (1) hook at each end for intermediate levels.
4. Medium duty or heavier beams: 12 or 13 gauge HRS must be used top and bottom. Minimum two (2) hooks each end.
5. Shelves: 5/8" thick industrial grade 42 lbs. test particle board and be designed to take the loading specified in the construction notes. Additional capacities per level achieved by use of shelf supports and tie bars.
6. Endframes: consisting of two (2) posts and required number of frame connectors to give a capacity of 9000 lbs. per endframe.
7. Installation: No nuts & bolts or clips required.  
Four (4) basic components only: Upright, Frame connector, Beams and Shelves. Shelves are adjustable on 2" centres. Frame connectors have two (2) hooks at each end for easy squaring. Beams have double hooks on each end are tight fitting for rigidity. Shelves are easily adjustable, even after assembly. Particle board is the same size for Easyup 7000 and Easyup 5000 series. Slot screwdriver for turning Tabs and Safety lock and mallet are the only tools needed to assemble.
8. Strength: Strong enough for Mezzanines and High-Rise applications. Four (4) types of beams to a maximum capacity of 2,000 lbs UDL. Posts may be doubled for High-rise and Multi-tier Mezzanines.